

## Agglomerate (Polished) Pre-Grouting Sealing

**Purpose** To protect porous cement or resinous man-made stone from grout staining and ease grout cleanup.

Finished Look Desired	Level of Stain Protection	Product Options	# Coats	Approx. Coverage Per Coat per gallon (3.785 L)	Cure Time Prior to Grouting	Interior	Exterior	Notes
Natural Look	Premium	<b>Stone Sealer's Choice</b>	1	95 m <sup>2</sup>	2 hours	Yes	N/A	Recommended in food preparation or serving areas or where maximum stain protection is required.
	Premium	<b>Ultra-Solv</b>	1	95 m <sup>2</sup>	2 hours	Yes	N/A	
Natural Look	Standard	<b>Pro Solv 10</b>	1	95 m <sup>2</sup>	2 hours	Yes	N/A	Provides limited protection in food preparation and serving areas.
	Economical	<b>Stone Sealer</b>	1	95 m <sup>2</sup>	2 hours	Yes	N/A	
<b>Darkened Color Enhancement</b>	Premium	<b>Enrich'N'Seal</b>	1	95 m <sup>2</sup>	2 hours	Yes	N/A	Use only on unsealed Agglomerate surfaces. Not recommended on impervious, resinous Agglomerate.

- Procedure**
1. The product selected for pre-grouting sealing should also be used for sealing.
  2. Ensure surface is clean and dry.
  3. Apply per product directions.
  4. Always grout and clean a small test area to determine desired results.
  5. Grout and cleanup per manufacturer's directions ensuring that no grout residue is left on Agglomerate surface.

These recommendations are intended as general guidelines for pre-grouting sealing porous Agglomerate.

**Read product directions thoroughly prior to use. Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.**

### Technical Assistance

1. Call +61 2 9521 4000
2. Visit our website [www.aquamix.com.au](http://www.aquamix.com.au)
3. Email [technical@aquamix.com.au](mailto:technical@aquamix.com.au)

## Agglomerate (Polished) Sealing

**Purpose** To protect porous cement or resinous man-made stone from sub-surface staining and ease ongoing maintenance.

Finished Look Desired	Level of Stain Protection	Product Options	# Coats	Approx. Coverage Per Coat per gallon (3.785 L)	Grout Cure Time Prior to Sealing	Expected Wear	Interior	Exterior	Notes
Natural Look	Premium	<b>Stone Sealer's Choice</b> Water-Based	1-2	110 m <sup>2</sup> - 140 m <sup>2</sup>	48 hours	Up to 15 Years	Yes	N/A	Recommended in food preparation or serving areas or where maximum stain protection is required.
	Premium	<b>Ultra-Solv</b>	1-2	110 m <sup>2</sup> - 140 m <sup>2</sup>	48 hours	Up to 15 Years	Yes	N/A	
Natural Look	Standard	<b>Pro Solv 10</b>	1-2	110 m <sup>2</sup> - 140 m <sup>2</sup>	48 hours	Up to 10 Years	Yes	N/A	Provides limited protection in food preparation and serving areas.
	Economical	<b>Stone Sealer</b>	1-2	110 m <sup>2</sup> - 140 m <sup>2</sup>	48 hours	Up to 5 Years	Yes	N/A	
<b>Darkened Color Enhancement</b>	Premium	<b>Enrich'N'Seal</b>	1	140 m <sup>2</sup>	48 hours	Up to 15 Years	Yes	N/A	Use only on unsealed porous Agglomerate for darkened color enhancement and seal.

- Procedure**
1. Ensure surface is clean and dry.
  2. Apply per product directions.
  3. Ready for surface traffic 2 hours after final sealer application. Keep area dry for 12 hours.

These recommendations are intended as general guidelines for sealing Porous Agglomerate Stone.

**Read product directions thoroughly prior to use. Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.**

### Architectural Specification

In each part of the CSI format specification for the tile or stone installation, the following is recommended:

1. **In Part 1:** Submittals - Submit copy of the Manufacturer's literature for the selected Aqua Mix product (s) from the above chart including a Material Safety Data Sheet and Product Label.
2. **In Part 2:** Material Section – Include Aqua Mix product (s) from the chart above, 250 Benjamin Drive, Corona, CA 92879.
3. **In Part 3:** After the cleaning section add a section for sealing. Apply product from chart above according to label instructions and handle product according to the Material Safety Data Sheet.

### Technical Assistance

1. Call +61 2 9521 4000
2. Visit our website [www.aquamix.com.au](http://www.aquamix.com.au)
3. Email [technical@aquamix.com.au](mailto:technical@aquamix.com.au)

## Agglomerate (Polished) Finishing

**Purpose** To provide and maintain a protective wear-layer and enhance surface sheen.

Function	Product Options	Alternative Products	Dilution Ratio	Expected Coverage	Interior	Exterior	Notes
Protect Factory Polish on Floor Areas	StonEndure System	N/A	Use undiluted	N/A	Yes	N/A	Designed for spray buff protection/maintenance using high RPM floor buffing machine with white nylon pad.
Protect Factory Polish on Countertops & Walls	Stone Clean & Shine	Brilliance	Use undiluted to spray & polish	N/A	Yes	N/A	Designed for easy spray & polish application using a soft cloth. Brilliance is a non-spray, apply & wipe.

**Note: No sealer is required under the StonEndure system as this is a sealer/finish system**

- Procedure**
1. Sweep, dust or vacuum surface.
  2. Apply and buff per product directions.

These recommendations are intended as general guidelines for finishing and protecting Polished, Sealed, Agglomerate Stone.

**Read product directions thoroughly prior to use. Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.**

### Architectural Specification

In each part of the CSI format specification for the tile or stone installation, the following is recommended:

1. **In Part 1:** Submittals - Submit copy of the Manufacturer's literature for the selected Aqua Mix product (s) from the above chart including a Material Safety Data Sheet and Product Label.
2. **In Part 2:** Material Section – Include Aqua Mix product (s) from the chart above, 250 Benjamin Drive, Corona, CA 92879.
3. **In Part 3:** After the cleaning section add a section for sealing. Apply product from chart above according to label instructions and handle product according to the Material Safety Data Sheet.

### Technical Assistance

1. Call +61 2 9521 4000
2. Visit our website [www.aquamix.com.au](http://www.aquamix.com.au)
3. Email [technical@aquamix.com.au](mailto:technical@aquamix.com.au)

## Agglomerate (Polished) Maintenance

**Purpose** To safely maintain a clean agglomerate stone and grout surface and to preserve the stone's beauty and integrity.

Type of Maintenance	Product Options	Alternative Products	Dilution Ratio	Expected Coverage Per Gallon (3.785 L)	Notes
Routine: Floors	Stone Cleaner	Concentrated Tile Cleaner	30 – 118 ml per 3.785 L water	930 m <sup>2</sup> – 1,860 m <sup>2</sup>	Highly-concentrated. Neutral pH. Safe for regular use.
Routine: Countertops & Walls	Stone Clean & Shine	Brilliance	Use undiluted	N/A	Designed for spray & polish cleaning of countertops and walls. Brilliance is non-spray, apply & wipe.
Periodic Heavy-Duty	Stone Deep Clean	Heavy-Duty Tile & Grout Cleaner	Add up to 4 parts water	45 m <sup>2</sup> – 55 m <sup>2</sup>	Contains no acid. Safe on agglomerate stone & grout.
Antibacterial/Disinfectant	Tile Plus More Antibacterial Cleaner	N/A	Use undiluted	N/A	Quick spray-and-wipe cleaner & disinfectant.

**Note:** For StonEndure system use the full system maintenance products.

- Procedure**
1. Sweep, dust mop or vacuum surface.
  2. Mix and apply per product directions.

These recommendations are intended as general guidelines for maintaining Agglomerate Stone.

**Read product directions thoroughly prior to use. Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.**

### Technical Assistance

1. Call +61 2 9521 4000
2. Visit our website [www.aquamix.com.au](http://www.aquamix.com.au)
3. Email [technical@aquamix.com.au](mailto:technical@aquamix.com.au)