

# Surface Care & Maintenance Guide

## Granite - Honed

### Pre-Grouting Sealing

**Purpose** To protect porous surface from grout staining and ease grout cleanup.

Desired Finish and Level of Stain Resistance	Product Options	# Coats	Approx. Coverage per coat per 3.785 L	Cure Time Prior to Grouting	Notes
Natural Look, No Sheen Premium	<b>Sealer's Choice™ Gold</b>	1	75m <sup>2</sup>	2 hours	Recommended in food areas or where <b>maximum</b> stain protection is required.
	<b>Ultra-Solv™</b>	1	75m <sup>2</sup>	2 hours	
Natural Look, No Sheen Standard	<b>Pro Solv™</b>	1	75m <sup>2</sup>	2 hours	Provides limited protection in food areas. Use where <b>standard</b> stain protection is required.
Natural Look, No Sheen Economical	<b>Penetrating Sealer</b>	1	75m <sup>2</sup>	2 hours	Provides limited protection in food areas. Use where <b>basic</b> stain protection is required.
Colour Enhanced, No Sheen, Premium	<b>Enrich'N'Seal</b>	1	95m <sup>2</sup>	2 hours	Use only on unsealed surface for darkened color enhancement and seal.

**Note** The product selected for pre-grouting sealing should also be used for sealing.

**Helpful Tip** Add Aqua Mix Grout Haze Clean Up to last bucket of clean water used in grout cleanup. This will facilitate removal of remaining grout residue on surface.

### Sealing

**Purpose** To protect porous surface from staining and ease ongoing maintenance.

Desired Finish and Level of Stain Resistance	Product Options	# Coats	Approx. Coverage per coat per 3.785 L	Grout Cure Time Prior to Sealing	Notes
Natural Look, No Sheen Premium	<b>Sealer's Choice™ Gold</b>	2	95-110m <sup>2</sup>	48 hours	Recommended in food areas or where <b>maximum</b> stain protection is required.
	<b>Ultra-Solv™</b>	2	95-110m <sup>2</sup>	48 hours	
Natural Look, No Sheen Standard	<b>Pro Solv™</b>	2	95-110m <sup>2</sup>	48 hours	Provides limited protection in food areas. Use where <b>standard</b> stain protection is required.
Natural Look, No Sheen Economical	<b>Penetrating Sealer</b>	2	95-110m <sup>2</sup>	48 hours	Provides limited protection in food areas. Use where <b>basic</b> stain protection is required.
Colour Enhanced, No Sheen, Premium	<b>Enrich'N'Seal™</b>	2	95-110m <sup>2</sup>	48 hours	Use only on unsealed surface for darkened color enhancement and seal.

### Maintenance

**Purpose** To safely maintain a clean surface and to preserve it's beauty and integrity.

Type of Maintenance	Product	Dilution Ratio	Approx. Coverage per coat per 3.785 L	Notes
Routine	<b>Concentrated Stone &amp; Tile Cleaner</b>	30 – 118 ml per 3.785 L water	930 m <sup>2</sup> – 1,860 m <sup>2</sup>	Highly-concentrated. Neutral pH. Safe for regular use.
Periodic Heavy-Duty	<b>Heavy Duty Tile &amp; Grout Cleaner OR Stone Deep Clean</b>	Add up to 4 parts water	45 m <sup>2</sup> – 55 m <sup>2</sup>	Contains no acid. Safe on stone & grout. Will remove wax-type finishes.
Periodic Heavy-Duty Large Commercial Areas	<b>1 &amp; 2 Deep Clean</b>	60-120 ml of powder and liquid to 10 L of water	743 m <sup>2</sup> – 2,973 m <sup>2</sup>	Recommended for large commercial areas. Will remove wax-type finishes

These recommendations are intended as general guidelines for pre-grout sealing, sealing and maintenance.

Read product directions thoroughly prior to use. Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.

**For Architectural specifications please contact Aqua Mix Australia.**