

Surface Care & Maintenance Guide

Travertine - Cross Cut

Pre-Grouting Sealing

Purpose To protect porous surface from grout staining and ease grout cleanup.

| Desired Finish and Level of Stain Resistance | Product Options | # Coats | Approx. Coverage per coat per 3.785 L | Cure Time Prior to Grouting | Notes |
|--|------------------------------------|---------|---------------------------------------|-----------------------------|--|
| Natural Look, No Sheen Premium | Sealer's Choice™ Gold | 1 | 55-75m ² | 2 hours | Recommended in food areas or where maximum stain protection is required. |
| | Ultra-Solv™ | 1 | 55-75m ² | 2 hours | |
| Natural Look, No Sheen Standard | Pro Solv™ | 1 | 55-75m ² | 2 hours | Provides limited protection in food areas. Use where standard stain protection is required. |
| Natural Look, No Sheen Economical | Penetrating Sealer | 1 | 55-75m ² | 2 hours | Provides limited protection in food areas. Use where basic stain protection is required. |
| Low-Medium Sheen Premium | Seal & Finish Low Sheen | 1 | 55-75m ² | 2 hours | Use only on unsealed, textured porous surfaces. |
| High Sheen (Interior only) Premium | High Gloss Sealer | 1 | 55-75m ² | 2 hours | Use only on highly textured porous surfaces. Interior only. |
| Colour Enhanced, No Sheen Premium | Enrich'N'Seal | 1 | 55-75m ² | 2 hours | Use only on unsealed surface for darkened color enhancement and seal. |

Note The product selected for pre-grouting sealing should also be used for sealing.

Helpful Tip Add Aqua Mix Grout Haze Clean Up to last bucket of clean water used in grout cleanup. This will facilitate removal of remaining grout residue on surface.

Sealing

Purpose To protect porous surface from staining and ease ongoing maintenance.

| Desired Finish and Level of Stain Resistance | Product Options | # Coats | Approx. Coverage per coat per 3.785 L | Grout Cure Time Prior to Sealing | Notes |
|--|--|---------|---------------------------------------|----------------------------------|---|
| Natural Look, No Sheen Premium | Sealer's Choice™ Gold | 2 | 75-95m ² | 48 hours | Recommended in food areas or where maximum stain protection is required. |
| | Ultra-Solv™ | 2 | 75-95m ² | 48 hours | |
| Natural Look, No Sheen Standard | Pro Solv™ | 2 | 75-95m ² | 48 hours | Provides limited protection in food areas. Use where standard stain protection is required. |
| Natural Look, No Sheen Economical | Penetrating Sealer | 2 | 75-95m ² | 48 hours | Provides limited protection in food areas. Use where basic stain protection is required. |
| Low-Medium Sheen, Premium | Seal & Finish Low Sheen | 2-3 | 75-95m ² | 48 hours | Use only on unsealed, textured porous surfaces. |
| High Sheen (Interior only) Premium | Seal & Finish Low Sheen with Floor Shine & Hardener | 2-3 | 75-95m ² | 48 hours | For high-sheen on interior areas, apply Floor Shine & Hardener after final application of Seal & Finish Low Sheen |
| | | 2 | 75-95m ² | 48 hours | |
| High Sheen (Interior only) Premium | High Gloss Sealer | 2-3 | 75-95m ² | 48 hours | Use only on highly textured porous surfaces. Interior only. |
| Colour Enhanced, No Sheen Premium | Enrich'N'Seal™ | 2 | 75-95m ² | 48 hours | Use only on unsealed surface for darkened color enhancement and seal. |

Maintenance

Purpose To safely maintain a clean surface and to preserve it's beauty and integrity.

| Type of Maintenance | Product | Dilution Ratio | Approx. Coverage per coat per 3.785 L | Notes |
|--|--|---|---|---|
| Routine | Concentrated Stone & Tile Cleaner | 30 – 118 ml per 3.785 L water | 930 m ² – 1,860 m ² | Highly-concentrated. Neutral pH. Safe for regular use. |
| Periodic Heavy-Duty | Heavy Duty Tile & Grout Cleaner OR Stone Deep Clean | Add up to 4 parts water | 45 m ² – 55 m ² | Contains no acid. Safe on stone & grout. Will remove wax-type finishes. |
| Periodic Heavy-Duty Large Commercial Areas | 1 & 2 Deep Clean | 60-120 ml of powder and liquid to 10 L of water | 743 m ² – 2,973 m ² | Recommended for large commercial areas. Will remove wax-type finishes |

These recommendations are intended as general guidelines for pre-grout sealing, sealing and maintenance.

Read product directions thoroughly prior to use. Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.

For Architectural specifications please contact Aqua Mix Australia.