

## Removal of Sealer Residue from Tile or Stone Surfaces

**For Removal of Aqua Mix:** Penetrating Sealer, Pro-Solv, Ultra-Solv, Grout Sealer, Sealer's Choice Gold.

**Purpose:** To remove sealer residue that has been allowed to cure on tile or stone surface.

### Method

**Product:** Aqua Mix **Poultice** (Note A).

**Equipment:** **Aquabug Cleaning Kit** or White nylon scrub pad, mop and bucket with wringer or wet-dry vacuum.

Optional: Low RPM (150 - 350 RPM) floor machine utilizing a white nylon pad.

**Coverage:** Approximately 5 m<sup>2</sup> – 10 m<sup>2</sup> per 0.338 kg jar

**Procedure:**

1. Always test a small area first to ensure satisfactory results.
2. Protect surrounding areas from splattering to minimize cleanup.
3. Pre-wet surface with water.
4. Sprinkle Aqua Mix **Poultice** onto a manageable area of up to 1 m<sup>2</sup> making a thin slurry.
5. Spread mixture onto surface and agitate using the **Aquabug Cleaning Kit** or with low RPM (150 - 350) floor machine using a white nylon pad. Keep surface wet throughout buffing process.
6. Remove solution with clean towels or sponge and rinse twice with clean water. A wet-dry vacuum may be used.
7. Polish surface dry with clean, dry towels or buff with soft lambs wool pad.

**Note A:** Procedure may be done by hand or by machine.

### Technical Assistance:

1. Call +61 2 9521 4000
2. Visit our web site [www.aquamix.com.au](http://www.aquamix.com.au)
3. Email all technical questions to [technical@aquamix.com.au](mailto:technical@aquamix.com.au)

This recommendation is intended as a guideline for the removal of sealer residue. The actual cleaning requirements may vary depending on type of tile, method of application and amount of residue.

**Read product directions thoroughly prior to use.**

**Always test first. Keep surface clean and dry to reduce possibility of slip-fall accidents.**